

Presence detector + air quality sensor

Multisensor True Presence®

The ultimate sense organ for modern building management.

- Sensor with the most detection sizes from our product portfolio
- 360° True Presence® detection with Ø 9 m
- 177 m² presence area with one sensor
- Available with IP, DALI-2 IPD and BT-IPD interface
- Networking and commissioning via app via Bluetooth or interface-specific via DALI bus or IP web interface
- Very easy to install thanks to magnetic modular system

 Bluetooth®
MESH



 New measurand: Noise level	 Other output values: Infection risk (IP, BT IPD), stale air and dew point.	 Commissioning, setting and networking via free STEINEL Connect App	 Cross-range networking of STEINEL Bluetooth Mesh products
--	---	---	--

Presence detector + air quality sensor

Multisensor True Presence®



Infection risk (IP, BT IPD), stale air and dew point	High-frequency sensor 360°	Radius max. 15m	True Presence	Brightness (lx)
			Technical data Multisensor True Presence® Dimensions, flush-mounted 123x123x51 mm Dimensions, surface-mounted 142x142x45 mm Assembly Ceiling Mounting height 2-12 m Angle of coverage 360° Capture True Presence® Ø 9 m Capture Presence Ø 15 m Capture Movement Ø 15 m DALI-2 IPD (230V), Flush-mounted (Q1/23) 4007841 081829 DALI-2 IPD (230V), Surface-mounted (Q1/23) 4007841 081812 IP, Flush-mounted 4007841 081867 IP, Surface-mounted 4007841 081850 BT-IPD, Flush-mounted 4007841 084127 BT-IPD, Surface-mounted 4007841 084110	
Further variants				
		New STEINEL Connect App for Bluetooth Mesh Connect Standard		GET IT ON Google Play Download on the App Store