

Hallway

The specialist for long hallways and corridors.

Designed to match the Control PRO II family, the Hallway presence detector leaves a visibly lasting impression in modern buildings. Providing a detection zone of 25x3 m, it guarantees a fast switching response. Ideal for use in long hallways and corridors. Bluetooth takes the effort out of setting them up, putting them into operation and interconnecting them.



 Bluetooth Mesh for fast and energy-saving connections	 Temperature measuring with the bus interfaces IP, DALI-2 IPD and KNX	 Humidity measuring with the bus interfaces IP, DALI-2 IPD and KNX
--	---	--

High-frequency hallway & corridor presence detector

Hallway



	 Detection zone 25 x 3 m radial, digitally adjustable per direction	 Mounting height 4 m max.	Hallway technical specifications Mounting height:2.00 – 4.00 m Reach, radial & tangential..... 25 x 3 m Ordering details (concealed installation) COM1 4007841 086503 COM1 (black) 4007841 086336 COM2 4007841 086350 DALI-2 APC 4007841 086299 DALI-2 IPD..... 4007841 086398 KNX V3.1 4007841 086527 KNX V3.1 (black)..... 4007841 086480 IP 4007841 086435 BT IPD (Slave) 4007841 086282 Ordering details (surface installation) COM1 4007841 086329 COM1 (black) 4007841 086312 COM2 4007841 086343 DALI-2 APC 4007841 058012 DALI-2 IPD..... 4007841 086367 KNX V3.1 4007841 086459 KNX V3.1 (black) 4007841 086442 IP 4007841 086404 BT IPD (Slave) 4007841 086275 Ordering details (recessed) COM1 4007841 086497 KNX V3.1 4007841 086510 Ordering details (Zubehör) Surface-mounting adapter 4007841 063887
 Settings via Steinel Connect app	 Interfaces		
 UV protected material			